





Neural Networks Based Graphics

Generative Models


About me

- Daniel Roich
- Masters student under Dani's supervision
- Fell in love with NN based graphics at the the 3rd year of B.S.C thanks to participating in the Sadna
- PTI – Pivotal Tuining Inversion



Our plan



The background features a large, irregular watercolor shape in shades of light blue and teal. Below this, there's a lighter green watercolor shape. Scattered around these shapes are numerous small, dark blue dots of varying sizes. A thin, dark blue line curves across the right side of the image, ending in a small, stylized, wavy shape.

01

Neural Networks

Neural Networks recap

What is learning

- Data – (X, y)
- Goal – learn a function $f: X \rightarrow y$
- Examples – Classification, Regression, Object Detection and Image Captioning




A cat sitting on a suitcase on the floor

Unsupervised Learning




Figure copyright Ian Goodfellow, 2016. Reproduced with permission.

1-d density estimation



2-d density estimation

- Data – X
- Just data, no labels
- Goal – learn some underlying hidden structure of the data
- Examples – Clustering, density estimation and feature learning

The background features a large, irregular watercolor shape in shades of light blue and teal, centered on the page. Below this, there's a lighter green watercolor shape. Scattered around these shapes are numerous small, dark blue dots of varying sizes. A thin, dark blue line starts from the top right, curves around the central shape, and ends in a series of loops on the right side.

02

VAE

Variational Auto Encoders

Generative Models

Why are deep generative models useful?
Why are deep generative models useful?
Why are deep generative models useful?

Text
description

This flower has
petals that are
white and has
pink shading

This flower has
a lot of small
purple petals in
a dome-like
configuration

This flower has
long thin
yellow petals
and a lot of
yellow anthers
in the center


This flower is
pink, white,
and yellow in
color, and has
petals that are
striped

This flower is
white and
yellow in color,
with petals that
are wavy and
smooth

This flower has
upturned petals
which are thin
and orange
with rounded
edges



This flower has
petals that are
dark pink with
white edges
and pink
stamen

256x256
StackGAN



Generating Models

- Real data distribution:





- Create new data drawn from the same distribution
- **Any distribution** in d dimensions can be generated by taking a set of d variables that are **normally distributed** and **mapping** them through a sufficiently complicated function

Maximum likelihood

- Maximize likelihood of training data:

$$\theta^* = \arg \max_{\theta} \mathbb{E}_{x \sim p_{\text{data}}} \log p_{\text{model}}(x \mid \theta)$$



Example:

Data: generated from a Gaussian distribution with a variance of 4, and an **unknown** mean.

One may think of MLE as taking the Gaussian, sliding it over all possible means, and choosing the mean which causes the model to fit the data best.

<https://towardsdatascience.com/maximum-likelihood-estimation-984af2dcfcac>

generative models

explicit density
function



implicit density
function

VAE
(Variational
Auto Encoder)

GAN
(Generative
Adversarial Net)

Autoencoders

- Unsupervised learning – comparing output to input
- Finding a lower dimensional representation of the input




Why do we need a latent space?

- Original data contains unmeaningful representation
- Latent features capture meaningful data representation



Autoencoder Loss




$$L = \| D(E(X)) - x \|_2$$

Reconstruction Loss



How can we use an autoencoder to generate new data?

- Sample data from the latent space and reconstruct new images




How can we use an autoencoder to generate new data?

- Sample data from the latent space and reconstruct new images
- Can we do that with regular autoencoders?
 - Latent space not continuous
 - Hard to interpolate between points




Solution – Variational Auto Encoders

- Make a continuous latent space
- Sample from the latent distribution to receive new data




VAE

Kingma et al. - 2014




VAE Flow




Difference between autoencoder (deterministic) and variational autoencoder (probabilistic).

VAE

- Same image can be encoded in different ways
- Creates a continuous space
- Close points have similar meaning





AE




VAE

Latent Space Arithmetic



Summary-VAE

- Allows using autoencoder for data generation
 - Explicitly models the density function
 - Finds meaningful data features
 - Disadvantage – blurry outcomes, both generative and reconstructive
-
- What if we give up modeling the density function?




03

GAN

Generative Adversarial Network


2 player game



Dive deeper

Discriminators Goal?

Generators Goal?



$$\min_G \max_D V(D, G) = \mathbb{E}_{x \sim p_{\text{data}}(x)} [\log D(x)] + \mathbb{E}_{z \sim p_z(z)} [\log(1 - D(G(z)))].$$

$$\min_G \max_D V(D, G) = \mathbb{E}_{\boldsymbol{x} \sim p_{\text{data}}(\boldsymbol{x})} [\log D(\boldsymbol{x})] + \mathbb{E}_{\boldsymbol{z} \sim p_{\boldsymbol{z}}(\boldsymbol{z})} [\log(1 - D(G(\boldsymbol{z})))].$$

How to Train?

Training Procedure

$$\min_G \max_D V(D, G) = \mathbb{E}_{\mathbf{x} \sim p_{\text{data}}(\mathbf{x})} [\log D(\mathbf{x})] + \mathbb{E}_{\mathbf{z} \sim p_z(\mathbf{z})} [\log(1 - D(G(\mathbf{z})))].$$

Alternate between:


1. Gradient Acent on Discriminator

$$\max_{\theta_d} \left[\mathbb{E}_{x \sim p_{data}} \log D_{\theta_d}(x) + \mathbb{E}_{z \sim p(z)} \log(1 - D_{\theta_d}(G_{\theta_g}(z))) \right]$$


2. Gradient Decent on Generator

$$\min_{\theta_g} \mathbb{E}_{z \sim p(z)} \log(1 - D_{\theta_d}(G_{\theta_g}(z)))$$


What its like to train a GAN




Training plot



My First Experience



GANs History




GAN




Yellow boxes are real data samples that are nearest matches to last column of fake images. This shows the generator didn't merely memorize training examples

GAN



DCGAN



DCGAN



BigGAN



Figure 1: Class-conditional samples generated by our model.

BigGAN



StyleGAN



Super Resolution

original



bicubic
(21.59dB/0.6423)



SRResNet
(23.44dB/0.7777)




SRGAN
(20.34dB/0.6562)



Image To Image Translation



More Image To Image (because it's amazing)



Applications Overview



Conditional Image Generation

SOTA results. Photorealistic image generation and many use-cases



Creating Larger Datasets

Opens new opportunities as data became critical resource in many open problems

Stability

Hard to train as the process is at times unstable and does not reach nash equilibrium




Mode Collapse

Stuck in mode collapse – the Generator outputs the same image all the time. **Why?**



Auction

Edmond de Belamy Sold for \$432,500



Why I chose to show
you this?



05

Editing

Editing Images Using GANs



Generative Adversarial Networks (GANs)



2014



2015



2016



2017



2018



2019

Random images




<https://thispersondoesnotexist.com/>

Random images



<https://thesecatsdonotexist.com/>

Baseline Progressive GAN



StyleGAN2-ADA (2020)

- ArXiv: <https://arxiv.org/abs/2006.06676>
- PyTorch implementation: <https://github.com/NVlabs/stylegan2-ada-pytorch>
- TensorFlow implementation: <https://github.com/NVlabs/stylegan2-ada>
- MetFaces dataset: <https://github.com/NVlabs/metfaces-dataset>

StyleGAN2 (2019)

- ArXiv: <https://arxiv.org/abs/1912.04958>
- Video: <https://youtu.be/c-NJtV9Jvp0>
- TensorFlow implementation: <https://github.com/NVlabs/stylegan2>




StyleGAN (2018)

- ArXiv: <https://arxiv.org/abs/1812.04948>
- Video: <https://youtu.be/kSLJriaOumA>
- TensorFlow implementation: <https://github.com/NVlabs/stylegan>
- FFHQ dataset: <https://github.com/NVlabs/ffhq-dataset>




Progressive GAN (2017)

- ArXiv: <https://arxiv.org/abs/1710.10196>
- Video: <https://youtu.be/G06dEcZ-QTg>
- TensorFlow implementation: https://github.com/tkarras/progressive_growing_of_gans
- Theano implementation: https://github.com/tkarras/progressive_growing_of_gans/tree/original-theano-version
- CelebA-HQ dataset: https://github.com/tkarras/progressive_growing_of_gans#preparing-datasets-for-training

StyleGAN Architecture





StyleGAN's style inputs correspond to
different levels of details:
coarse, medium, fine





Control: pose, hair, face shape

StyleGAN's style inputs correspond to
different levels of details:
coarse, medium, fine



Control: facial features, eyes

StyleGAN's style inputs correspond to
different levels of details:
coarse, medium, [fine](#)



Control: lighting, color scheme

Not all is perfect



Why StyleGAN?



Original



Age




Eyeglasses




Gender




Pose




Original




+Illumination



+Pose




-Age



+Expression




Original



$E(\mathbf{v}_{20}, 6)$

+Wrinkles




$E(\mathbf{v}_{57}, 7-8)$

+Hair Color



$E(\mathbf{v}_{23}, 3-5)$

+Expression



$E(\mathbf{v}_{27}, 8-17)$

+Overexpose

It has been show that the $\mathcal{W}$ latent space is disentangled and offers editing capabilities

InterFaceGAN (2019)
StyleFlow (2020)
GANSpace (2020)

What is Disentanglement?

No formal definition which is widely accepted

Proposed definition: a change in a single underlying factor of variation in the sample x should lead to change in a single factor in the learned representation $r(x)$

Example - Rectangles

$z = (\text{height}, \text{width}, \text{color})$

Latent Space

(10, 20, red)

(10, 10, red)

(10, 20, orange)



Desired Domain Space






Editing Applications


Creative content generation

Latent space editing




**Can we perform meaningful
manipulations on Real
images?**


Can we perform meaningful manipulations on Real images?



$$I \in \mathbb{R}^{3 \times 256 \times 256}$$

End Goal






Inversion




$$\begin{pmatrix} w_1 \\ w_2 \\ w_3 \end{pmatrix}$$

$$I \in \mathbb{R}^{3 \times 256 \times 256}$$



$$I \in R^{3 \times 256 \times 256}$$




$$w' \in R^{512}$$



$$\begin{pmatrix} \epsilon_1 \\ \epsilon_2 \\ \epsilon_3 \end{pmatrix}$$

Learned smile direction



$$I \in \mathbb{R}^{3 \times 256 \times 256}$$

Inversion


$$\begin{pmatrix} w_1 \\ w_2 \\ w_3 \end{pmatrix}$$


editing

$$\begin{pmatrix} w_1 + \epsilon_1 \\ w_2 + \epsilon_2 \\ w_3 + \epsilon_3 \end{pmatrix}$$

$$w' \in \mathbb{R}^{512}$$

StyleGAN





$$I \in \mathbb{R}^{3 \times 256 \times 256}$$

Inversion



$$\begin{pmatrix} w_1 \\ w_2 \\ w_3 \end{pmatrix}$$


editing

$$\begin{pmatrix} w_1 + \epsilon_1 \\ w_2 + \epsilon_2 \\ w_3 + \epsilon_3 \end{pmatrix}$$

$$w' \in \mathbb{R}^{512}$$

StyleGAN





$$I \in \mathbb{R}^{3 \times 256 \times 256}$$

Inversion

$$\begin{pmatrix} w_1 \\ w_2 \\ w_3 \end{pmatrix}$$



editing

$$\begin{pmatrix} w_1 + \epsilon_1 \\ w_2 + \epsilon_2 \\ w_3 + \epsilon_3 \end{pmatrix}$$


$$w' \in \mathbb{R}^{512}$$




StyleGAN



Current Latent Space



Extend The Latent Space



Extend The Latent Space

$w \in \mathcal{W} +$
(18 × 512)

*PreTrained
StyleGAN*



$w \in \mathcal{W} +$





$w \in \mathcal{W}$




source

Image2StyleGAN (2020)

Inversion Drawbacks





$$I \in \mathbb{R}^{3 \times 256 \times 256}$$

Inversion





$$\begin{pmatrix} w_1 \\ w_2 \\ w_3 \end{pmatrix} \xrightarrow{\text{editing}} \begin{pmatrix} w_1 + \epsilon_1 \\ w_2 + \epsilon_2 \\ w_3 + \epsilon_3 \end{pmatrix}$$

$$w' \in \mathbb{R}^{512}$$




StyleGAN



InterFaceGAN
Interpreting the Latent Space of
GANs for Semantic Face Editing
(2020)
Yujun Shen, et al

Demo



Original



Age

Eyeglasses


Gender

Pose


Assumptions




Method



Method




Assumptions Visualization




Method

$$\mathbf{w}_1 \rightarrow \mathbf{w}_1 + \alpha \mathbf{n} = \mathbf{w}_2$$




*SeFa - Closed-Form
Factorization of Latent
Semantics in GANs (2020)
Yujun Shen, Bolei Zhou*

Demo




Method



$$A(w) = Aw + b$$

$$A(w') = A(w + \alpha n) = Aw + b + \alpha An$$

Method



$$A(w) = Aw + b$$

$$A(w') = A(w + an) = Aw + b + \alpha An$$


$$n^* = \operatorname{argmax}_{\{n \in \mathbb{R}^d : n^T n = 1\}} \|An\|_2^2$$

SeFa advantage over InterFaceGAN



InterFaceGAN advantage over SeFa





$$I \in \mathbb{R}^{3 \times 256 \times 256}$$

Inversion



$$\begin{pmatrix} w_1 \\ w_2 \\ w_3 \end{pmatrix}$$

editing





$$\begin{pmatrix} w_1 + \epsilon_1 \\ w_2 + \epsilon_2 \\ w_3 + \epsilon_3 \end{pmatrix}$$

$$w' \in \mathbb{R}^{512}$$



StyleGAN



Play at home

<https://github.com/danielroich/PTI>

https://colab.research.google.com/github/danielroich/PTI/blob/main/notebooks/inference_playground.ipynb

Text driven image manipulation



Inversion



A tanned woman



A woman without makeup

Text driven image manipulation



Inversion



A man with a beard



A blonde man

Editing



Editing




Editing



Pivotal Tuning for Latent-based editing of Real Images



PTI Idea



Results



Results



NN Based Graphics Future

